



So	RF
do 3500	1200
3501 - 4000	1400
4001 - 5000	1600
5001 - 6000	1800
6001 - 7000	2000

D	Distance between foundation baskets
F	Foundation length
RF	Space between the moving carriages
S0	Drive way opening
A	Gate leaf length $A=S0+RF+400$

1	Wire outlet point: 3x1,5mm ² ; 3x0,5mm ²
2	Anchor bolt made of ribbed bar 20-A-II with 500 mm length
3	Foundation - gravelled concrete B20 condensed
4	Below freezing zone level in accordance with standard PN-81/B-03020
5	2x0,5mm ² steering wires for photo cells in PVC or steel pipe
6	Power supply: 3x1,5mm ² for 230V (1phase). Perform the installation in accordance with standard PN-IEC 60364 "electric installation in buildings"
7	3x0,5mm ² switch steering
8	Axis of the moving gate leaf
9	Dimensions in accordance with the table
10	Safe distance from constant obstacle
11	Connect wires with assembly reserve 1500 [mm]
12	4x0,5mm ² (photo cells)
13	Infrared barrier
14	Finished entry level
15	Mounting opening size
16	Theoretical fence post
Notes:	1. Level the foundation anchor ends
	2. Keep the vertical level when setting the foundation anchors
	3. Do not change the section of the power and steering wires
W	Premises point view

				Ważne dla	
Projekował	Data	Nazwisko	Podpis	Sliding gate PI 95	
Konstruował	11/03/05	S. Ziobrowski			
Sprawdził	03/03/05	S. Ziobrowski			
		K. Kotal			
Podziałka	1:1	Nazwa Rysunku	Foundation of the sliding gate PI 95 - right		
				Nr Rysunku AW.97.11346	
FPH Wiśniewski 33-311 Wiśniewo tel. (018) 44 77 111 fax. (018) 44 77 110 http://www.wisniewski.pl				Data Aktualizacji: 28.07.2006	
				Skala: 1/1 Format: A4	

All rights reserved